

OE14-376/377



KONGSBERG



January 2015

LIGHT RING COLOUR CAMERA

- **Integral high output LED lighting**
- **Ruggedised 3,000 msw aluminium alloy housing**
- **Electronic iris**
- **Compact dimensions**

The compact colour camera with integral LED lighting is available with both PAL (OE14-376) and NTSC (OE14-377) video outputs. The camera is housed in a ruggedised yet light weight and compact 3000 msw depth rated Aluminium Alloy housing.

The camera boasts a unique front port design which prevents light from the 10 integral LEDs reflecting back into the lens. This feature, in combination with auto shuttering and AGC functions, provides the user with truly impressive light compensation without the cost and inconvenience of an additional lamp.

The camera is ideally suited to close proximity inspection tasks such as gauge and process monitoring, ROV manipulator wrist applications and tooling applications.

The camera is optionally available with a right angle viewing adaptor which provides the user with a cost effective solution for inspection of confined entry areas such as narrow diameter pipe walls, tanks and cavities.

Applications

- Tooling
- ROV Manipulator Wrist camera
- Pipe Wall Inspection
- Gauge and Process Monitoring

TECHNICAL SPECIFICATIONS

Performance

Horizontal Resolution	480 TVL/PH
Light Sensitivity	100 mV video at 20×10^{-3} lux faceplate 350 mV video at 90×10^{-3} lux faceplate
Minimum Scene Illumination	0.28 lux
Signal to Noise Ratio	>56 dB (weighted)

Electrical

Scan Standard	625 lines 50Hz PAL (OE14-376) 525 lines 60Hz NTSC (OE14-377)
Sensor Elements	752 (H) x 582 (V) (OE14-376) 768 (H) x 492 (V) (OE14-377)
Video Output	1V pk –pk composite video, into 75Ω
Power Input	12 to 24 V dc, 220mA (350mA max), with LEDs turned on
Light Output	99 lux at 1 meter

Optical

Lens	4.3 mm, F1.8
AOV in water	Horizontal: 36° Vertical: 27.5° Diagonal: 43.5°
Iris Control	CCD Electronic
Focus Range	300mm to Infinity, Fixed

Mechanical

Dimensions	Diameter: 45mm Length: 96mm (excl. connector)
Weight	In air 0.37Kg, in water 0.21Kg
Housing Material	Anodised aluminium alloy HE30T6 to BS1474
Connector	Subconn BH4M (or equivalent)

Environmental

Operating Depth	3,000 msw
Temperature	Operating: -5 to 40°C , Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration
Vibration	10G, from 20 to 150Hz in all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2007 and BS EN 61000-6-1: 2007

Features

White Balance	Factory preset to 5,600K
---------------	--------------------------

Options

Titanium Housing (6,000 msw)
Right Angle Viewing Adaptor

Specifications subject to change without any further notice.

KONGSBERG MARITIME

Telephone: +44 1224 226500

E-mail sales: km.camsales.uk@kongsberg.com

E-mail support: km.camsupport.uk@kongsberg.com

www.km.kongsberg.com



KONGSBERG